

DSAS001/DSDS001



DSAS001/DSDS001 Shore durometer



Features

- Testing rubber, plastic, leather and all other soft materials
- Fast and easy to read
- Large digital display, digits 8mm high
- Supplied as standard with UKAS certificate of calibration
- Portable
- Use by hand or mounted on a stand
- Available in Shore A or Shore D

- Supplied with a reference block
- Data output for SPC
- Power on/off automatic
- Electronic module protection to IP65, even with data output
- According to DIN 53505, ASTM D2240, ISO R/868
- Can be used in conjunction with Shore bench stand

Technical specifications

Shore A or Shore D
0.1 unit
Conforms to DIN 53505,
ASTM D2240 and ISO R/868
0-100
ø18mm
A scale blunt taper 35°
D scale sharp point 30°
ø1.25mm
Lithium 3V, CR2032
RS-232 combined with external power supply

Standard delivery

- Instrument
- Button battery
- Reference block
- Blunt taper 35° penetrator (A scale)
- Sharp point 30° penetrator (D scale)
- UKAS certificate of calibration
- Carrying case
- Manual

Optional accessories

- Bench stand
- Communication cable
- Reference block
- Software




DSAS001 Handheld digital durometer for Shore A

hardness testing

DSDS001 Handheld digital durometer for Shore D

hardness testing

SHA0003 Bench stand









Represented by:

IN10-146 231214

CORPORATE HEAD OFFICE

INNOVATEST Europe BV MANUFACTURING, DISTRIBUTION & SERVICE

Borgharenweg 140

6222 AA Maastricht (The Netherlands)

Phone: +31 43 3520060 +31 43 3631168 Fax:

E-mail: info@innovatest-europe.com Website: www.innovatest-europe.com

BRANCHE OFFICES

INNOVATEST Benelux BVBA SALES & SERVICE

Phone: +32 12 779002 +32 12 779003 Fax:

E-mail: info@innovatest-benelux.com Website: www.innovatest-europe.com

INNOVATEST Shanghai Co., Ltd. ASIA & CHINA SALES & SERVICE

Building 2, No.123, 1165 Nong Jindu Road,

South Metropolis Industrial Park

Minhang District, Shanghai, P.R. China

Zip code: 201108

E-mail: info@innovatest-shanghai.com Website: www.innovatest-shanghai.com Changes in products and/or product specifications can emerge due to new technologies and continuous development.

We reserve the right to change or modify specifications of products without prior notice.

We recommend you to contact our sales office for up-to-date information.

© All rights reserved