




TECHNICAL PARAMETERS Vibration exciter S 59320/*-340

Rated peak force Sine _{pk} /Random _{RMS} /Shock _{pk} ¹	20000/18000/60000 N
Frequency range	5 - 3000 Hz
Main resonance frequency	> 2400 Hz
Max. displacement Peak-Peak	50.8 mm
Max. velocity Sine/Random/Shock	2.0/1.8/2.5 m/s
Max. acceleration Sine/Random/Shock ¹	82/65/163 g
Suspension stiffness	150 N/mm
Effective moving mass	25.0 kg
Max. weight tested	410 kg
Weight with trunnion RIT/AIT/LB*	1650/1850/1550 kg
Magn. stray field std./low degaussing	< 1.5/< 0.8 mT
Armature diameter	340 mm
Required compressed air supply	Min. 600 kPa
Interlocks	Temperature, displacement, cooling air, overcurrent, compressed air

¹) theoretical maximum shock value. Depends on payload, amplifier, shock and shock width
* RIT, AIT or LB



SCOPE OF DELIVERY, OPTIONS AND FEATURES OF THE SYSTEM

Scope of delivery:
Vibration exciter 20 kN
Trunnion mount (AIT, RIT or LB)
Power amplifier 22.5 kVA
Cooling blower
Connection cables (each 10 m)
Power cables (10 m)
for amplifier (CEE 63 connector)
Blower hose Ø150 mm (5 m)
Compressed-air hose NW 7,2 (Standard) (5 m)

Options:
AIT-Swivel trunnion
with integrated vibration isolation
RIT-Swivel trunnion
LB-frame
Different hole pattern of armature
(different pitch diameter and/or thread inserts)
at customers request
Low degaussing kit to further reduce stray magnetic field
Wheels&Rails (incl. 3m rails)
Thermobarrier (-40°C to +140°C)
Chamber leadthrough
Climatic chamber support kit
Remote control (Software)
Silencer
for cooling blower (Noise reduction 6 - 10 dB(A))
Acoustic enclosure
for cooling blower (Noise reduction 5 - 23 dB(A))
Cable extension
Factory acceptance test

Options:
TIRA EMS Energy Management System

Operation with temperature-controlled cooling blower (and optional with variable field strength)

Features:
Vibration isolation < 3 Hz (AIT)
< 6 Hz (RIT;LB)
Coarse filter unit
Fully automatic pneumatic load compensation
AIT fixable
Automatic centering of the AIT-System and the armature
Degauss kit to reduce stray magnetic field
Made in Germany
Servicehotline

TECHNICAL PARAMETERS Amplifier A 3 07 3 034

Output power _{RMS}	22500 VA
Frequency range	DC - 4 kHz
Voltage _{RMS} , max.	150 V
Current _{RMS} , max.	225 A
Signal input voltage _{RMS} (switchable)	2.5/5/10 V
Distortion	< 0.7 %
Signal to noise ratio	> 90 dB
Field voltage, max.	85 V
Field current, max.	85 A
Weight	615 kg
Dimensions (WxHxD)	600 x 2200 x 800 mm
Power supply (Standard)	3~ / N / PE 400 V±5% 50 Hz, CEE 63
Recommended fuse protection (Standard)	63 A slow
Max. power consumption at 400 V (incl. blower)	30 KVA
Interlocks:	Overload, temperature, clipping and more
Features:	
High Signal to noise ratio of >90 dB	Lo-Field/Hi-Field button (Energy-saving mode)
Field supply integrated	Noise-button
Mains switch and integrated line filter	Input voltage analyzer
ESD-monitoring	Voltage clipping limiter to avoid clipping
(Protection of the system against damage)	3 Sigma peak current
Field voltage/Field current variable according to customer spec.	

TECHNICAL PARAMETERS Cooling blower TB 8

Volume flow rate	max. 3300 m³/h
Total pressure difference	max. 5.2 kPa
Power	5.5 kW
Frequency	50 Hz
Hose diameter	150 mm
Hose length (Std.)	5 m
Weight	127 kg
Dimensions (WxHxD)	841 x 916 x 592 mm
Sound pressure level, max.	93 dB(A)
Power supply (standard)	by amplifier rack
Max. power consumption at 400 V	8 kVA
Options:	
Silencer TB 8-SI (Noise reduction 6 - 10 dB(A))	Dimensions (LxD): 1200 x 340 mm
	Weight: 3.3 kg
Acoustic enclosure TB 8-AE (Noise reduction 5 - 23 dB(A))	Dimensions (WxHxD): 1179 x 1271 x 1094 mm
	Weight: 134 kg
	Hose length according to customers request (up to 10 m)



Cooling blower TB 8



Silencer TB 8-SI (optional)



Acoustic enclosure TB 8-AE (optional)