



**9 KERN KFP-V40**

Weighing bridge

STANDARD FACTORY

IP 68 2 DAYS M

- Weighing bridge entirely made of stainless steel, extremely resistant to bending because of its high material thickness
- **F** Weighing plate fixed with stainless steel screws, for easier access to the loadcells from above
- 4 load cells, stainless steel, encapsulated, IP68, OIML-R60-approved, class III, 3000 e
- Can be built in using pit frames (optional)
- Level indicator and levelling feet for precise levelling of the scale
- Comfortable levelling of the weighing bridge from the top
- Accessories see KERN BFN, page 109

**10 KERN KFD-V40**

Weighing bridge

STANDARD FACTORY

IP 68 2 DAYS M

- Weighing bridge made from stainless steel, two integrated access ramps, extremely resistant to bending
- Extremely flat construction to facilitate access: access height only 45 mm
- 4 load cells, stainless steel, encapsulated IP68, OIML-R60-approval for verification, class III, 3000 e
- Level indicator and levelling feet for precise levelling of the scale
- Accessories see KERN NFN, page 117



Model	Weighing range [Max] kg	Readability [d] g	Verification value [e] g	Min. load [Min] g	Cable length approx. m	Net weight approx. kg	Weighing plate W×D×H mm	Price excl. VAT, ex works €
<b>9 Stainless steel weighing bridge KFP-V40</b>								
KFP 600V40SM	600	200	200	4000	5	95	1000×1000×80	2680,-
KFP 1500V40M	1500	500	500	10000	5	135	1500×1250×80	3460,-
KFP 1500V40SM	1500	500	500	10000	5	95	1000×1000×80	2700,-
KFP 3000V40M	3000	1000	1000	20000	5	135	1500×1250×80	3800,-
<b>10 Stainless steel weighing bridge KFD-V40</b>								
KFD 600V40M	600	200	200	4000	5	130	1600×1200×78	2700,-
KFD 1500V40M	1500	500	500	10000	5	130	1600×1200×78	2700,-