





## Practical hanging scale for rapid, mobile weighing

## Features

- With the TÜV certification mark, the scales meet the requirements of the standard EN 13155 (Non-fixed load lifting attachments/ breakage resistance) and EN 61010-1 (Electrical safety)
- Ideal for rapid control in goods-in and goods-out
- Also essential in the private sector to determine the weight of fish, game, fruits, bicycle parts, suitcases etc.
- Hold function: For easy reading of the weighing result, the display can be "frozen" in different ways. Either automatically when the weighing value remains unchanged or manually by pressing the Hold key
- Hook, steel, can be hinged

15

• Peak load display (peak hold)

## Technical data

- · LCD display, digit height 12 mm
- Ready for use: Batteries included, 2×1.5 V AAA, operating time up to 180 h
- Further weighing units: kg, lb, N
- Permissible ambient temperature 5 °C/35 °C

## Accessories

Image: Bar and the set of the

| STANDARD | OPTION |      |      |     |       |         |
|----------|--------|------|------|-----|-------|---------|
|          | C      | ^    |      |     |       | DAkkS   |
| CAL EXT  | UNIT   | MOVE | BATT | DMS | 1 DAY | +3 DAYS |

| Model      | Weighing capacity | Readability | Dimensions housing | Net weight | Price        | Option                    |      |
|------------|-------------------|-------------|--------------------|------------|--------------|---------------------------|------|
|            |                   |             | W×D×H              |            | excl. of VAT | DAkkS Calibr. Certificate |      |
|            | [Max]             | [d]         |                    | approx.    | ex works     | DAkkS                     |      |
| KERN       | kg                | g           | mm                 | kg         | €            | KERN                      | €    |
| HDB 5K5N   | 5                 | 5           | 72×25×105          | 0,20       | 60,-         | 963-127H                  | 82,- |
| HDB 10K10N | 10                | 10          | 72×25×105          | 0,20       | 60,-         | 963-128H                  | 99,- |