











Features

- Especially suitable for weighing patients in wheelchairs because of the low-profile platform which can be approached from either side
- II The large steel weighing plate also makes it ideal for weighing obese patients
- Ideal also for rapid weighing of, e.g. laundry carts, container trolleys, roller containers, etc.
- Secure and non-slip positioning with height-adjustable rubber feet
- 2 Level indicator to level the balance precisely
- Hold function:

When patients do not stand or sit completely still, a stable weight is calculated using an average weight and this is then "frozen". This means that you have sufficient time to attend to the patient first and then read the weight

- BMI function to determine underweight/ normal weight/surplus weight
- If the scale can be easily transported using the two handles and two rollers and does not require much storage space
- · Wall mount for the display device
- · Protective working cover included in delivery

Technical data

- · Large backlit LCD display, digit height 25 mm
- Dimensions of display device W×D×H 200×130×60 mm
- Overall dimensions,
 W×D×H 1050×1050×100 mm
- Batteries included, 6×1,5 V AA, operating time up to 40 h
- · Cable length of display device approx. 300 cm
- Net weight approx. 55 kg

Accessories

- Protective working cover over the display device, scope of delivery: 5 items, KERN MBC-A06S05, € 40,-
- Cleaning cloths, alcohol-free cleaning cloths for wipe disinfection, quick-acting, on basis of modern quaternary ammonium compounds, and also against papova viruses. Particularly gentle on materials, and therefore very well suited for the disinfection of alcohol sensitive products. Fulfill the legal requirements for occupational safety in accordance with TRGS 525/540. Packaging contents 80 pcs., size 20×22 cm per cloth, KERN MYC-01, € 55,-
- · For more details see the internet

CAL EXT IP 65 BATT DMS 2 DAYS

1				
Model	Weighing range	Readability	Weighing surface	Price excl. of VAT
	[Max]	[d]		ex works
KERN	kg	kg	mm	€
MWB 300K-1	300	0,1	800×800	850,-