



ATESTOR
www.atestor.hu

Compact, robust drive-through scale – particularly mobile thanks to its carrying handle, rollers and lightweight construction

Features

- Drive-through scale for rapid weighing of e.g. wire cage trolleys, shelf trolleys, container trolleys, storage trolleys, sack trucks, transpallets, mobile containers, containers refuse etc.
- Low platform height and integrated access ramps on both sides facilitate access. No need for pit frame installation – which saves money
- **1** Weighing bridge: Steel, powder coated, 4 silicon-coated aluminium load cells with protection against dust and water splashes to IP67
- **2** Level indicator to level the balance precisely
- **3** The scale can be easily transported using rollers and a handle and does not require much storage space
- Wall mount for the display device, as standard, only for models without a stand
- Protective working cover included with delivery
- **4** Did you know? Our floor scales are delivered in a robust wooden box. This protects the high-quality weighing technology from environmental influences and stresses during transportation. KERN – always one step ahead

Technical data

- Large LCD display, digit height 25 mm
- Platform height in the drive-through area: 40 mm
- Dimensions weighing surface, steel, painted WxD 800x800 mm (Without ramps) WxDxH 1000x1000x40 mm
- Dimensions of display device WxDxH 235x114x51 mm
- Cable length of display device approx. 5 m
- Optional battery operation, 4x1.5 V AA not included in scope of delivery, operating time up to 60 h
- Permissible ambient temperature -10 °C/40 °C

Accessories

- Protective working cover over the display device, scope of delivery: 5 items, KERN EOB-A04BS05, **€ 44,-**
- Pair of base plates to fix the weighing bridge to the floor, KERN BIC-A07, **€ 44,-**

11

STANDARD								OPTION	
								1	

Model	Weighing capacity [Max] kg	Readability [d] kg	Net weight approx. kg	Price	Option	
				excl. of VAT ex works €	DAkkS Calibr. Certificate DAkkS KERN	Certificate €
KERN						
NIB 300K-1	300	0,1	40	890,-	963-129	139,-
NIB 600K-2	600	0,2	40	890,-	963-130	196,-