

Pallet scale with steel load support (IP67) and the best price-to-performance ratio

Features

STANDARD

- High mobility: thanks to battery operation, compact, lightweight construction, it is suitable for the use in several locations
- II Load support: steel, powder coated, 4 silicone-coated aluminium load cells, protection against dust and water splashes IP67
- Image: The scale can be easily transported using rollers and a handle and does not require much storage space
- Protective working cover included with delivery
- Did you know? Our floor scales are delivered in a robust wooden box. This protects the high-quality weighing technology from environmental influences and stresses during transportation. KERN – always one step ahead

Technical data

OPTION

- Large LCD display, digit height 25 mm
 Dimensions of display device W×D×H
- 235×114×51 mm
- Cable length of display device approx. 5 m
 Optional battery operation, 4×1.5 V AA not
- included in scope of delivery, operating time up to 60 h
- Permissible ambient temperature -10 °C/40 °C







ATESTOR www.atestor.hu

Accessories

- Protective working cover over the display device, scope of delivery: 5 items, KERN EOB-A04BS05, € 44,-
- Stand to elevate display device, height of stand approx. 1000 mm, KERN EOB-A02B, € 142,-

Shipment via freight forwarder. Please ask for dimensions, gross weight, shipping costs

	MOVE IP67 BATT MULTI DMS 2 DAYS	DARKS +3 DAYS				
Model	Weighing capacity	Readability	Net weight	Price excl. of VAT	Option DAkkS Calibr. Certificate	
	[Max]	[d]	approx.	ex works	DAkkS	
KERN	kg	kg	kg	€	KERN	€
UIB 600K-1	600	0,2	55	1110,-	963-130	196,-
UIB 1.5T-4	1500	0,5	55	1110,-	963-130	196,-
UIB 3T-3	3000	1	55	1110,-	963-132	520,-